

API Programmer Guide

1. imprint(Revision V1.00).

* All rights reserved, Specifications subject to change without notice.

2. explain of backtrack value.

2.1 the function return values

0x00	Command OK. (success)
0x01	Command FAILURE, the error code is:
0x02	checksum error.
0x03	Not selected COM port
0x04	time out reply
0x05	check sequence error
0x07	Receive error
0x0A	the parameter value out of range

2.2 System Error/Status Codes (0x80-0xFF)

0x80	SET OK. (success)
0x81	SET FAILURE
0x82	Reader reply time out error
0x83	the card do not exist
0x84	the data is error
0x85	the authentication failure
0x86	Unknown Internal Error
0x89	operation error
0x8f	Reader received unknown command
0x90	show the card could not support this command
0x91	show the command format have a mistake
0x92	show the command could not support OPTION form
0x93	show the inputed block is inexistence.

0x94	show the inputed block had been locked
0x95	show Locked the block is not successful
0x96	show the write card operation is not successful.

3 System Commands

3.01 HANDLE API_OpenComm(
char *com,
int Baudrate);

Description

Open the comm port and set the baud rate for further communication with the reader.

Example

Select COM1 and set the baud rate to 115200bps.

```
int Baudrate=115200;
handle comhandle;    { the 'comhandle' is the serial port handle.}
comhandle=API_OpenComm("COM1",Baudrate);
if (comhandle<>0)
{    //successful    }
else
{ //Not successful }
```

Input Parameter Description

Com Character pointer to C string of the name of the serial port where the reader is connected. (e.g. COM1, COM2, COM3, COM4)

Baudrate The communication baud rate of serial port
(Possible values : 9600, 19200, 38400, 57600, 115200).

Output Parameter

none

Return value:

HANDLE , succeed to open the serial port handle
if you open it succeed, the return value is the serial port handle.
if you open it unsuccessfull, the return value is 0.

```
3.02 int API_CloseComm( const HANDLE commHandle);
```

Description

Close the communication port. The API_CloseComm () should be called to release the serial port before closing the application program.

Input Parameter Description

CommHandle you need to close the serial port handle

Output Parameter

None

Return value:

0 ☐ closed the serial port in the handle

-1 ☐ inputted the handle value is 0, it couldn't close.

```

3.03 int    API_SetDeviceAddress(
                                HANDLE    commHandle,
                                int       DeviceAddress,
                                unsigned char newAddr,
                                unsigned char *buffer);

```

Description: set the new address for reader,the reader back to the setting address

Input Parameter Description

commHandle, the serial port handle

DeviceAddress, formerly system address

newAddr, new system address

*buffer buffer send a pointer, it is used to return the received value.

Output Paramete

If Command success

*buffer the read date(It means you have set the new address in this function)

If Command Failure

*buffer System Error/Status Codes(You can consult the 2.2)

Return value:

0x00	Command OK. (success)
------	------------------------

0x01	Command FAILURE
------	-----------------

```

3.04 int API_SetBaudrate(
                                HANDLE      commHandle,
                                int         DeviceAddress,
                                unsigned char newBaud,
                                unsigned char *buffer);

```

Description:

set up the baud rate between the reader and PC communication. the baud rate will be saved in EEPROM and it will be a new default baud rate

Input Parameter Description

commHandle	the serial port handle
DeviceAddress	equipment address
newBaud,	require set new baud rate.
baud rate code:	
0x00	– 9600 bps
0x01	– 19200 bps
0x02	– 38400 bps
0x03	– 57600 bps
0x04	– 115200 bps
*buffer	introduction a finger,back to the received date.

Output Paramete

If Command success

*buffer[] new baud rate(It means set new baud rate code in this function)

□ 0x00 – 9600 bps □ 0x01 – 19200 bps □ 0x02 – 38400 bps □ 0x03 – 57600 bps □ 0x04 – 115200 bps □

If Command Failure

*buffer System Error/Status Codes(You can consult the 2.2)

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE

```

3.05 int API_SetSerNum( HANDLE      commHandle,
                        int         DeviceAddress,
                        unsigned char *newValue,
                        unsigned char *buffer);

```

Description:

set 8 byte serial number which be supplied by manufactory

Input Parameter Description□

commHandle the serial port handle
DeviceAddress equipment address
*newValue 8 byte serial number
*buffer buffer send a pointer, it is used to return the received value.

Output Paramete:

If Command Failure
*buffer System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)
0x01 Command FAILURE

```
3.06 int API_GetSerNum(  
                                HANDLE        commHandle,  
                                int            DeviceAddress,  
                                unsigned char *buffer);
```

Description:

read one byte reader address and 8 byte serial number which be supplied by
manufactory

Input Parameter Description□

commHandle the serial port handle
DeviceAddress equipment address
*buffer buffer send a pointer, it is used to return the received value.

Output Paramete:

*buffer buffer[0] reader address
 buffer[1...8] 8 byte reader serial number

Return value:

0x00 Command OK. (success)
0x01 Command FAILURE

```
3.07 int WriteUserInfo(HANDLE    commHandle,  
                        int        DeviceAddress,  
                        int        num_blk,  
                        int        num_length,  
                        char        *user_info);
```

Description:

the reader consist of 4 blocks(each block less than 120 byte),the user data space in all 480 byte. the user could base the requirement to deposited the relevant userinfo into the reader.

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
num_blk	the block number
num_length	data length
*user_info	user information

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE

```
3.08 int ReadUserInfo(HANDLE commHandle,
                      int DeviceAddress,
                      int num_blk,
                      int num_length,
                      char *user_info);
```

Description:

Read the data from the reader, the reader consist of 4 blocks
(each block less than 120 byte)

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
int num_blk	the block number
int num_length	data length
*user_info	wait for reading user data

Output Paramete:

*user_info	If Command Failure,then user_info[0] is error code.
	If Command success,then user_info[0..N] is information read user

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE

```

3.09 int  GetVersionNum(HANDLE    commHandle,
                           int      DeviceAddress,
                           char      *VersionNum);

```

Description:

read reader version number

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

*VersionNum wait for reading version number

Output Paramete:

*VersionNum If Command Failure,thenVersionNum [0]is error code.
if Command success,thenVersionNum [0..N] is reading version number

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE

```

3.10 int  API_ControlLED(
                           HANDLE    commHandle,
                           int      DeviceAddress,
                           unsigned char freq,
                           unsigned char duration,
                           unsigned char *buffer);

```

Description: the work state of set light,include,light Cyc and repeating times

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

freq periodicity

duration	times
*buffer	wait for return value parameter

Output Paramete:

*buffer	If Command Failure,thenbuffer [0] □ is error code. If Command success ,then buffer [0] is 0x80
---------	---

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE

```

3.11  int  API_ControlBuzzer(
                                HANDLE          commHandle,
                                int             DeviceAddress,
                                unsigned char    freq,
                                unsigned char    duration,
                                unsigned char    *buffer);

```

Description: the work state of setting buzzer,include buzzer work Cyc and repeating times

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
freq	periodicity
duration	times
*buffer	wait for return value parameter

Output Paramete:

*buffer	If Command Failure,,thenbuffer [0] □ is error code. If Command success,then buffer [0] is 0x80
---------	---

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE

4 ISO14443 Type-A Commands

4.1 Type-A Commands

4.1.1 int MF_Request(
HANDLE commHandle,
Int DeviceAddress,
unsigned char inf_mode,
unsigned char *buffer);

Description: □ send ISO14443 A seeking card instruction

Input Parameter Description □

commHandle the serial port handle

DeviceAddress equipment address

mode seeking card mode

0x01 –Idle mode □ operate one card once a time □

0x00 –All mode □ operate a lot of card once a time □

*buffer wait for return value parameter

Output Paramete:

*buffer If Command FAILURE, then buffer [0] is error code.
if Command OK, then buffer [0..1] □ return data bunch within 2 byte

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE

4.1.2 int MF_Anticoll(
HANDLE commHandle,
int DeviceAddress,
unsigned char *snr,
unsigned char &status);

Description: □ test card quantity, single or much more, and then return the card number within 4 byte (if there are many cards, the only return one of card number)

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
Status	send a finger□ return to the number of the card
*snr	send a finger□ return to 4 byte card number

Output Paramete:

If Command success

Status	the checked card number(0x00 means have checked a single card,0x01 means have checked more cards
*snr	4 byte card number□ snr[0..3]□

If Command Failure

*snr	System Error/Status Codes(You can consult the 2.2)
------	--

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE

```
4.1.3 int MF_Select(  
                HANDLE commHandle,  
                int DeviceAddress,  
                unsigned char *snr);
```

Description:

Select card, make the card as been select stat...

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
*snr	send a finger,input 4 byte card number,and return to 4 byte card numbe

Output Paramete:

Status	checked card numbe
*snr	4 byte card number4□ snr[0..3]□

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE

```

4.1.4 int MF_Halt(
                HANDLE commHandle,
                int DeviceAddress );

```

Description:

select card,make the card as been break off

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

Output Paramete:

None.

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE

4.2 Mifare Appilication Commands

```

4.2.1 int API_PCDRead(HANDLE commHandle,
                      int DeviceAddress,
                      unsigned char mode,
                      unsigned char blk_add,
                      unsigned char num_blk,
                      unsigned char *snr,
                      unsigned char *buffer);

```

Description:

read the appointed length date at the appointed station

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

mode□ read mode

(Request Idle + Key A mode=00 , Request Idle + Key B mode= 02,
 Request All + Key A mode=01 , Request All + Key B mode=03□

□ the up number is hex□

blk_add□ read block address

num_blk□ read block amount

*snr□ a finger, transfer eight byte secret key
 *buffer wait receive the variable of output finger

Output Paramete:

If Command success

*snr□ 4 byte card number
 *buffer□ the read date (the fact number is□ num_blk*16)

If Command Failure

buffer[0] System Error/Status Codes(Youcan consult the 2.2)

Return value:

0x00 Command OK. (success)
 0x01 Command FAILURE

4.2.2 int API_PCDWrite(HANDLE commHandle,
 int DeviceAddress,
 unsigned char mode,
 unsigned char blk_add,
 unsigned char num_blk,
 unsigned char *snr,
 unsigned char *buffer);

Description:

Read-in date At appoint station

Input Parameter Description□

commHandle the serial port handle
 DeviceAddress equipment address
 mode□ needs write mode
 (Request Idle + Key A mode=00 , Request Idle + Key B mode= 02,
 Request All + Key A mode=01 , Request All + Key B mode=03□
 blk_add□ needs fill in block address
 num_blk□ needs fill in block number
 *snr□ wait fill in date
 *buffer□ afferent pointer sign to output the date

Output Paramete:

If Command success

snr[0..3]□ four byte card number

If Command Failure

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)
 0x01 Command FAILURE

4.2.3 int API_PCDInitVal(
 HANDLE commHandle,
 int DeviceAddress,
 unsigned char mode,
 unsigned char SectNum,
 unsigned char *snr,
 int value);

Description:

Initialize card

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

mode□ initialize mode

(Request Idle + Key A mode=00 , Request Idle + Key B mode= 02,
 Request All + Key A mode=01 , Request All + Key B mode=03□

SectNum, need initialize fan number

*snr, six byte secret key (introduction as pointer)

value 4 byte initialize the date

Output Paramete:

If Command success

snr[0..3] 4 byte card number

If Command Failure

snr[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE

```

4.2.4 int API_PCDDec(
                        HANDLE      commHandle,
                        Int          DeviceAddress,
                        unsigned char mode,
                        unsigned char SectNum,
                        unsigned char *snr,
                        int           *value);

```

Description:

Devalue work to the fan of the card

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

mode□ work mode

(Request Idle + Key A mode=00 , Request Idle + Key B mode= 02,
 Request All + Key A mode=01 , Request All + Key B mode=03□

SectNum, the fan number which need to write value 00-0F

*snr, 6 byte secret key□ introduction as pointer□

value need decrease value,4 byte length

Output Paramete:

If Command success

snr[0..3]□ 4 byte card number

value[0..3] date bunch after 4 byte work

If Command Failure

snr[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE

```

4.2.5 int API_PCDInc (
                        HANDLE      commHandle,
                        Int          DeviceAddress,
                        unsigned char mode,
                        unsigned char SectNum,
                        unsigned char *snr,
                        int           *value);

```

Description:

Add value work to appointed fan of the card.

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

mode□ work mode

(Request Idle + Key A mode=00 , Request Idle + Key B mode= 02,
 Request All + Key A mode=01 , Request All + Key B mode=03□

SectNum, need add value fan number 00-0F

*snr, 6 byte secret key(introduction as pointer)

value need add value, 4 byte length

Output Paramete:

 If Command success

 snr[0..3]□ 4 byte card number

 value[0..3] the date bunch after 4 byte work

 If Command Failure

 snr[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE

4.2.6 int GET_SNR (

 HANDLE commHandle,
 int DeviceAddress,
 unsigned char mode,
 unsigned char RDM_halt,
 unsigned char *snr
 unsigned char *value);

Description:

Return 1byte single card or numerous card sign□ 4 byte card number.

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

mode□ mode command □ mode command 26 or 52 □

0x52 –All mode□one time can work to many card□

```
00    don't need perform halt order
01    reader perform halt order
```

```
*snr,      returned 1byte single card or numerous card sign (if read card fail,return error code)
*value     return 4byte card number
```

Output Paramete:

If Command success

snr[0]	1 byte single card or numerous
value[0..3]	return 4 byte card number

If Command Failure

snr [0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00	Command OK. (success)
------	------------------------

0x01 Command FAILURE

```
4.2.7 int MF_Restore(HANDLE commHandle,
                    int DeviceAddress,
                    unsigned char mode,
                    int cardlength,
                    unsigned char *carddata );
```

Description:

According the selected mode to send the date

Input Parameter Description

commHandle	the serial port handle
------------	------------------------

DeviceAddress equipment address

mode□	mode command	0x00 —don't need check CRC
		0x01 —need check CRC

cardlength, card date length

```
*carddata,      send time□ card date□
                incept time□ return date□
```


Output Paramete:

If Command success

carddata[0..N], incept the return date

If Command Failure

carddata[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE

5. ISO14443 Type-B Commands

5.1 int RequestType_B(

 HANDLE commHandle,
 int DeviceAddress,
 unsigned char *buffer)

Description: this order perform REQB order of ISO14443B, get PUPI code of the card

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

*buffer, the date bunch after card reposition □ ATQB□

Output Paramete:

If Command success

 *buffer, the date bunch after card reposition □ ATQB□

 buffer[0] card reposition date length

 buffer[0..N] the date after work□ ATQB□

If Command Failure

 buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE

```

5.2 int AntiType_B(
                                HANDLE      commHandle,
                                int         DeviceAddress,
                                unsigned char *buffer);

```

Description: this order perform Anticol1B of ISO14443B

Input Parameter Description□

commHandle the serial port handle
DeviceAddress equipment address
*buffer, The date after return card □ ATQB□

Output Paramete:

If Command success

Buffer[0..N], the date of card return □ ATQB□

If Command Failure

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)
0x01 Command FAILURE

```

5.3 int SelectType_B (
                                HANDLE      commHandle,
                                int         DeviceAddress,
                                unsigned char *SerialNum);

```

Description:

this order perform ATTRIB of ISO14443B, distribute a sign for CID to the know card

Input Parameter Description□

commHandle the serial port handle
DeviceAddress equipment address
*SerialNum, the serial number of the card

Return value:

0x00 Command OK. (success)
0x01 Command FAILURE

```

5.4 int Request_AB(
                HANDLE      commHandle,
                int          DeviceAddress,
                unsigned char * buffer);

```

Description:

This order performance integration REQUEST AND ATTRIB order of ISO14443B, use one order to make card reposition.

Input Parameter Description□

commHandle the serial port handle
DeviceAddress equipment address
* buffer, return to 4 byte serial number of the worked card

Output Paramete:

If Command success
buffer[0..3], return to 4 byte serial number of the worked card
If Command Failure
buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)
0x01 Command FAILURE

```

5.5 int API_ISO14443TypeBTransCOSCcmd(
                                HANDLE      commHandle,
                                int          DeviceAddress,
                                unsigned char *cmd,
                                int          cmdSize,
                                unsigned char *buffer);

```

Description:

ISO14443 remit order, any effect order and date can be transfer by this order

Input Parameter Description□

commHandle the serial port handle
DeviceAddress equipment address
*cmd, date which wait to be send
cmdSize, date length
* buffer, return date

Output Paramete:

If Command success

buffer[0..N] the date which returned from the card

If Command Failure

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE

6 ISO15693 COMMANDS

```
6.1 int RDM_ISO15693_Inventory(  
                                HANDLE commHandle,  
                                int deviceAddress,  
                                unsigned char flag,  
                                unsigned char afi,  
                                const unsigned char *pData,  
                                unsigned char *nrOfCard,  
                                unsigned char *pBuffer);
```

Description:

This order is to get all the card's serial number which in the reading card district □ the gettable card number is relate to the output rate of the module antenna, commonly can read 2~6 card within anticollision□

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

flag, sign byte(length is 1 byte)

afi, AFI is date length

*pData, the sent date(the fact is a array, transfer by a pointer)

*nrOfCard the return card number(length is 1 byte)

*pBuffer the return date□ include LAG, DSFID and 8*n byte card number□

Output Paramete:

IF□ Command success (return 0x00)

*nrOfCard return card number (one byte)

*pBuffer return date□ include FLAG, DSFID and 8*n byte card number□

IF ☐ Command Failure (return 0x01)

*nrOfCard System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE, the error code is 2.2

6.2 int API_ISO15693Read (

HANDLE commHandle,
int DeviceAddress,
unsigned char flags,
unsigned char blk_add,
unsigned char num_blk,
unsigned char *uid,
unsigned char *buffer);

Description:

It's for reading 1 and numerous fan value. If need to read the safe digit of every block, make Option flag of FLAGS as 1 ,means FLAG=0x42,every fan will return 5 byte, include one byte show safe state and 4 byte block content, **here the most can read 12 block**, IF FLAG=02,will only return 4 byte block content, **here the most can read 63 block**.

Input Parameter Description ☐

commHandle	the serial port handle
DeviceAddress	equipment address
flags	0x02 without uid
	0x22 with uid
	0x42 without uid but need to read the safe digit
blk_add,	needed reading origin block number
num_blk,	block quantity
*uid	UID message
*buffer	return value

Output Paramete:

If : Command success (return 0x00)

*buffer return date

buffer[0] return flag

buffer[1..N] Data

buffer[0]	System Error/Status Codes(You can consult the 2.2)
-----------	--

0x00	Command OK. (success)
0x01	Command FAILURE, the error code is 2.2

Description: make writting work to every block(every time only can write one block)

commHandle	the serial port handle
DeviceAddress	equipment address
flags	0x02 without uid
	0x22 with uid
	0x42 without uid but need to read the safe digit
blk_add,	needed writting origin block number
num_blk,	writing block quantity
*uid	UID message
*buffer	return value

*buffer	return date
buffer[0]	return flag
buffer[1..N]	Data

buffer[0]	System Error/Status Codes(You can consult the 2.2)
-----------	--

```
0x00      Command OK. ( success)
0x01      Command FAILURE, the error code is:2.2
```

6.4 int API_ISO15693Lock(

```
HANDLE      commHandle,  
int          DeviceAddress,  
unsigned char flags,  
unsigned char num_blk,  
unsigned char *uid  
unsigned char *buffer);
```

Description: for lock block content, caution : this process can not in reverse(can not unlock) the content can not revise when the block be locked.

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
flags	0x02 without uid 0x42 without uid but need to read the safe digit 0x22 with uid
num_blk,	locked block number
*uid	UID message
*buffer	return value

Output Paramete:

If : Command success (return 0x00)□

buffer[0] return 0x80 □ means work ok.,

If : Command Failure (return 0x01)

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE, the error code is:2.2

6.5 int RDM_ISO15693StayQuiet(

```
HANDLE      commHandle,  
int          DeviceAddress,  
unsigned char flags,  
unsigned char *uid,  
unsigned char *buffer );
```

Description:

This order is to make the card to sleep state, must use the address mode if the sent data is same to the card serial number, after this work finish, the card will be sleep, otherwise the state will not change.

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
flags	sign byte 1byte
*uid	UID message
*buffer	return value

Output Parameter:

If : Command success (return 0x00)

buffer[0] return 0x80□ means work ok.

If : Command Failure (return 0x01)

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE, the error code is:2.2

6.6 int RDM_ISO15693Select(

HANDLE	commHandle,
int	DeviceAddress,
unsigned char	flags,
unsigned char	*uid,
unsigned char	*buffer) ;

Description:

This order must use address mode, if the sent data is same to the card serial number, after the work ok, the card will be selected, otherwise the state will not change

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
flags	sign byte 1 byte
*uid	UID message

*buffer return value

Output Paramete:

If : Command success (return 0x00)

buffer[0] return to 0x80□ means work ok

If : Command Failure (return 0x01)

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE, the error code is 2.2

6.7 int RDM_ResetToReady(

HANDLE	commHandle,
int	DeviceAddress,
unsigned char	flags,
unsigned char	*uid,
unsigned char	*buffer);

Description:

After the work ok, the card will return to Ready state .

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

flags sign byte 1 byte

0x02 without uid

0x42 without uid but need to read safe digit

0x22 with uid

*uid UID message

*buffer return value

Output Paramete:

If : Command success (return 0x00)

buffer[0] return 0x80□ means work ok

If : Command Failure (return 0x01)

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE, the error code is:

6.8 int RDM_WriteAFI(

HANDLE	commHandle,
int	DeviceAddress,
unsigned char	flags,
unsigned char	afi,
unsigned char	*uid,
unsigned char	*buffer);

Description:

Write AFI to the card .

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
flags	sign byt 1 byte
	0x02 without uid
	0x42 without uid but need to read the safe digit
	0x22 with uid
afi	wait write AFI
*uid	UID message
*buffer	return value

Output Paramete:

If : Command success (return 0x00)

buffer[0] return 0x80□ means work ok

If : Command Failure (return 0x01)

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE, the error code is:2.2

6.9 int RDM_LockAFI(

HANDLE	commHandle,
int	DeviceAddress,
unsigned char	flags,
unsigned char	*uid,
unsigned char	*buffer);

Description:

For lock AFI of the card, after lock AFI can not change

Input Parameter Description□

commHandle	the serial port handle
DeviceAddress	equipment address
flags	sign byte 1 byte
	0x02 without uid
	0x42 without uid but need to read the safe digit
	0x22 with uid
*uid	UID message
*buffer	return value

Output Paramete:

If : Command success (return 0x00)□

buffer[0] return 0x80□ means work ok

If : Command Failure (return 0x01)

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00	Command OK. (success)
0x01	Command FAILURE, the error code is:2.2

6.10 int RDM_WriteDSFID(

HANDLE	commHandle,
int	DeviceAddress,
unsigned char	flags,
unsigned char	DSFID,
unsigned char	*uid,
unsigned char	*buffer);

Description:

Write DSFID to the card

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

flags sign byte 1 byte

0x02 without uid

0x42 without uid but need to read the safe digit

0x22 with uid

DSFID the writted DSFID byte, the length is 1 byte

*uid UID message

*buffer return value

Output Paramete:

If : Command success (return 0x00)□

buffer[0] return 0x80□ means work ok

If : Command Failure (return 0x01)

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE, the error code is:

```
6.11                            int    RDM_LockDSFID(
                                HANDLE      commHandle,
                                int           DeviceAddress,
                                unsigned char flags,
                                unsigned char *uid,
                                unsigned char *buffer );
```

Description:

For lock DSFID of the card, after lock, DSFID can not change

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

flags sign byte (length is 1 byte)

0x02 without uid

0x42 without uid
0x22 with uid

*uid UID message
*buffer return value

Output Paramete:

If : Command success (return 0x00)□

buffer[0] return 0x80□ means work ok

If : Command Failure (return 0x01)

buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE, the error code is:2.2

6.12 int RDM_ISO15693_GetSysInfo(

HANDLE commHandle,
int deviceAddress,
unsigned char flag,
unsigned char *uid,
unsigned char *Buffer);

Description:

For get the particular message of the card, the fact content please refer to ISO15693 agreement date.

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

flags sign byte 1 byte

0x02 without uid

0x42 withou uid but need to read the safe digit

0x22 with uid

*uid UID message

*buffer return value

Output Paramete:

If : Command success (return 0x00)□

Then Buffer [0]: Flags

Buffer[1]: INFO Flags

Buffer[2..9]: UID

Buffer[10]: DSFID

Buffer[11]: AFI

Buffer[12..N]: Other fields

If : Command Failure (return 0x01)

Buffer[0] System Error/Status Codes(You can consult the 2.2)

Return value:

0x00 Command OK. (success)

0x01 Command FAILURE, the error code is:2.2

6.13 int RDM_ISO15693_GetMulSecurity(

HANDLE	commHandle,
int	deviceAddress,
unsigned char	flag,
unsigned char	blkAddr,
unsigned char	blkNum,
const unsigned char	*uid,
unsigned char	*pBuffer);

Description: for get the date of every safe state block of the card

Input Parameter Description□

commHandle the serial port handle

DeviceAddress equipment address

flag 0x02 without uid

0x22 with uid

0x42 without uid but need to read the safe digit

blkAddr, the read origin block number

blkNum, the read block quantity

*uid UID message

*pBuffer return value

Command FAILURE, the error code is:2.2